## NSN 5930-00-797-4938

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-797-4938

Thread	Class:
--------	--------

2b single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

3.240 inches

**Overall Height:** 

2.000 inches

**Overall Width:** 

2.000 inches

First Flat Length:

0.560 inches single actuator

Flat Height:

0.219 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.620 inches single actuator

**Individual Section Quantity:** 

1

## **Operating Tempurature Range:**

+0.0/+185.0 degrees celsius

## **Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section front

**Throw Quantity:** 

24 single section rear

**Mounting Method:** 

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

118.0 ac at sea level

**Mounting Facility Pattern:** 

Four position diamond single mounting facility

**Switch Actuator Indexing Position Quantity:** 

24 single actuator

**Shaft Type:** 

Round, flatted single actuator

## **NSN 5930-00-797-4938**Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
2.0 amperes resistive load ac at sea level
Style Designator:
Tap, square frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0