NSN 5930-00-797-7940

Rotary Switch - Page 1 of 2

0.496 inches single mounting facility

Thread Length:



View Online at https://aerobasegroup.com/nsn/5930-00-797-7940

| Hazardous Locations/environmental Protection: |
|--|
| Dustproof |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 1.375 inches single actuator |
| Individual Section Quantity: |
| 3 |
| Knob Manufacturer Code: |
| 10001 |
| Knob Manufacturer Part Number: |
| 4000-2 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical and nonpile-up nonsymmetrical |
| Pole Quantity: |
| 1 3rd section rear |
| Throw Quantity: |
| 7 3rd section rear |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 125.0 ac at sea level |
| Switch Actuator Indexing Position Quantity: |
| 7 single actuator |
| Shaft Type: |
| Round, square, threaded hole single actuator |
| Terminal Type: |
| Tab w/screw |
| Contact Switching Action: |
| Breaks before makes 3rd section rear |
| Switch Actuator Positioning Increment: |
| 45.0 degrees single actuator |
| Contact Load Current Rating: |
| 5.0 amperes resistive load ac at sea level |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5930-00-797-7940

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0