# NSN 5930-00-798-4813

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-798-4813

### **Thread Class:**

2a single mounting facility

### **Thread Length:**

0.359 inches single mounting facility and 0.391 inches single mounting facility

## **Overall Length:**

1.657 inches

#### **Overall Height:**

0.750 inches

## **Overall Width:**

1.125 inches

#### Shaft Diameter:

0.234 inches single actuator and 0.266 inches single actuator

#### Shaft Length:

0.359 inches single actuator and 0.391 inches single actuator

## Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

### Pole Quantity:

1 single section front

#### Throw Quantity:

6 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

6 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

## NSN 5930-00-798-4813

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

500.0 milliamperes resistive load dc at sea level

Style Designator:

Square wafer, panel mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0