NSN 5930-00-799-2157

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-799-2157

Thread Class:

2a single mounting facility

Thread Length:

0.310 inches single mounting facility

Overall Length:

2.004 inches

Overall Height:

1.120 inches

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.844 inches single actuator

Nonturn Device Radius:

0.250 inches at 6: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Pin at 6: 00 o'clock

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.312 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Turret

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

NSN 5930-00-799-2157

Rotary Switch - Page 2 of 2



Sty	ما	D	20	in	n	2	ŧ۸	r	
JLY	ı	יש	င၁	ıу	••	а	ιυ	ш	

In-line, cam actuated

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0