

View Online at <https://aerobasegroup.com/nsn/5930-00-799-3255>

Thread Class:

2a 2nd mounting facility

Thread Length:

0.688 inches 1st mounting facility

Overall Length:

6.125 inches

First Flat Length:

0.438 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.562 inches single actuator

Overall Diameter:

2.000 inches

Individual Section Quantity:

9

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section periphery

Throw Quantity:

4 each section periphery

Mounting Facility Circle Radius:

0.719 inches 2nd mounting facility

Mounting Method:

Threaded stud 2nd mounting facility

Thready Qty Per Inch (tpi):

40 2nd mounting facility

Thread Size:

0.469 inches 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Mounting Facility Pattern:

Three position circular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0