NSN 5930-00-799-3256

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-799-3256

Thread Class:

2a single mounting facility

Thread Length:

0.688 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

6.500 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.250 inches single actuator

Overall Diameter:

1.875 inches

Individual Section Quantity:

10

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 1st section periphery

Throw Quantity:

4 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-799-3256

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0