NSN 5930-00-799-3256

Rotary Switch - Page 1 of 2

0.688 inches single mounting facility

Hazardous Locations/environmental Protection:

Thread Class:

Thread Length:

Overall Length: 6.500 inches Shaft Diameter:

Shaft Length:

Dustproof

2a single mounting facility

0.250 inches single actuator

1.250 inches single actuator



View Online at https://aerobasegroup.com/nsn/5930-00-799-3256

Overall Diameter: 1.875 inches **Individual Section Quantity:** 10 **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 1st section periphery **Throw Quantity:** 4 each section periphery **Mounting Method:** Threaded bushing single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.469 inches single mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section periphery **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Switch Actuator Stop Device Type:**

Fixed stop single actuator

NSN 5930-00-799-3256

Rotary Switch - Page 2 of 2



| Contact | l nad | Current | Rating | |
|---------|-------|---------|--------|--|
| Cullact | Luau | Current | nauny | |

5.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0