## NSN 5930-00-799-3263

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-799-3263

#### **Body Style:**

Bushing mounted

#### Hazardous Locations/environmental Protection:

Humidity resistant

#### **Overall Length:**

0.680 inches

#### **Overall Height:**

2.630 inches

#### **Overall Width:**

0.780 inches

#### Bushing Length:

0.350 inches

#### **Body Length:**

0.680 inches

#### **Body Width:**

0.780 inches

### Body Height:

bouy neight.

2.150 inches

#### Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

#### Inclosure Type:

Fully enclosed

#### Mounting Method:

Threaded bushing

#### Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.625 inches

#### Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac

#### **Special Features:**

Push button and lamp not furnished

#### **Thread Series Designator:**

Unef

#### Terminal Type And Quantity:

6 turret and 2 tab, solder lug

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5930-00-799-3263

Push Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

