# NSN 5930-00-799-3290

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-799-3290

# **Body Style:**

Bushing mounted

# Hazardous Locations/environmental Protection:

Humidity resistant

# **Overall Length:**

1.183 inches

### **Overall Height:**

2.320 inches

# **Overall Width:**

0.780 inches

#### Bushing Length:

0.350 inches

#### Body Length:

1.183 inches

### Body Width:

0.780 inches

# Body Height:

Body Holght.

1.780 inches

# Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

#### Inclosure Type:

Fully enclosed

# Mounting Method:

Threaded bushing

#### Thready Qty Per Inch (tpi):

24

# Thread Size:

0.625 inches

# Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac

#### **Special Features:**

Lamp and push button not furnished

### **Thread Series Designator:**

Unef

# Terminal Type And Quantity:

12 turret and 2 tab, solder lug

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5930-00-799-3290

Push Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

