

View Online at <https://aerobasegroup.com/nsn/5930-00-800-1641>

**Thread Class:**

2a single mounting facility

**Overall Length:**

Between 10.939 inches and 11.314 inches

**Overall Height:**

5.125 inches

**Overall Width:**

2.750 inches

**First Flat Length:**

0.938 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

0.938 inches single actuator

**Individual Section Quantity:**

9

**Longest Horizontal Distance Between Mounting Centers:**

2.250 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.125 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

8 8th section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Bracket single mounting facility and threaded bushing single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from contact position 1 single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, nonparallel flatted single actuator

**Terminal Type:**

Turret

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0