

View Online at <https://aerobasegroup.com/nsn/5930-00-800-1641>

Thread Class:

2a single mounting facility

Overall Length:

Between 10.939 inches and 11.314 inches

Overall Height:

5.125 inches

Overall Width:

2.750 inches

First Flat Length:

0.938 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.938 inches single actuator

Individual Section Quantity:

9

Longest Horizontal Distance Between Mounting Centers:

2.250 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.125 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

8 8th section rear

Throw Quantity:

3 each section rear

Mounting Method:

Bracket single mounting facility and threaded bushing single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, nonparallel flatted single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0