

View Online at <https://aerobasegroup.com/nsn/5930-00-801-0120>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Body Diameter:**

1.000 inches

**Bushing Length:**

0.340 inches

**Body Length:**

1.000 inches

**Actuator Style:**

Round, threaded

**Actuator Height:**

1.240 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Switch Release Force:**

0.125 inch-ounces

**Switch Actuating Force:**

24.0 inch-ounces

**Actuator Movement:**

225.0 pretravel degrees and 0.188 overtravel inches and 0.062 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0