

View Online at <https://aerobasegroup.com/nsn/5930-00-801-0120>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

1.000 inches

Bushing Length:

0.340 inches

Body Length:

1.000 inches

Actuator Style:

Round, threaded

Actuator Height:

1.240 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Switch Release Force:

0.125 inch-ounces

Switch Actuating Force:

24.0 inch-ounces

Actuator Movement:

225.0 pretravel degrees and 0.188 overtravel inches and 0.062 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0