

View Online at <https://aerobasegroup.com/nsn/5930-00-801-1637>

Thread Class:

2b single mounting facility

Overall Length:

2.937 inches

Overall Height:

2.875 inches

Overall Width:

2.750 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.781 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.166 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.083 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.875 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

24 single section rear

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Push to turn

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0