NSN 5930-00-801-7238

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-801-7238

First Flat Length:

0.625 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.062 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Individual Section Quantity:

4

Knob Manufacturer Code:

10001

Knob Manufacturer Part Number:

9s534316

Longest Horizontal Distance Between Mounting Centers:

3.781 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.781 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Flange single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load dc at sea level

NSN 5930-00-801-7238

Rotary Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0