NSN 5930-00-802-2557

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-802-2557

·
Hazardous Locations/environmental Protection:
General purpose-nema type 1
Overall Length:
5.000 inches
Overall Height:
4.000 inches
Overall Width:
2.875 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Capillary Tube Length:
120.000 inches
Bulb Length:
8.250 inches
Bulb Diameter:
0.688 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
1.375 inches
Longest Vertical Distance Between Mounting Centers:
3.280 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
Between -100.0 degrees fahrenheit and 120.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
4.6 amperes resistive load third voltage
Contact Adjustability

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

NSN 5930-00-802-2557

Thermostatic Switch - Page 2 of 2



Contact	Adjustment	Range:

+25.00/+90.00 actuation point degrees fahrenheit and +23.00/+90.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0