NSN 5930-00-802-2784

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-802-2784

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.501 inches
Overall Height:
3.062 inches
Overall Width:
2.570 inches
First Flat Length:
0.560 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.470 inches single actuator
Unthreaded Mounting Hole Diameter:
0.185 inches single mounting facility
Individual Section Quantity:
2
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
4 each section front
Throw Quantity:
4 each section front
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
118.0 ac at sea level
Mounting Facility Pattern:
Two position diagonal single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, v flatted single actuator
Terminal Type:
Turret
Contact Switching Action:
Breaks before makes 1st section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-802-2784

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0