NSN 5930-00-802-2898

Rotary Switch - Page 1 of 2



30-00-802-2898

View Online at https://aerobasegroup.com/nsn/5930
Thread Class:
2a single mounting facility
Thread Length:
0.375 inches single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.593 inches
Overall Height:
1.250 inches
Overall Width:
1.250 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.437 inches single actuator
Nonturn Device Radius:
0.531 inches at 3: 00 o'clock
Individual Section Quantity:
1
Nonturn Device Type:
Tab at 3: 00 o'clock
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section rear
Throw Quantity:
3 single section rear
Mounting Method:
Threaded bushing single mounting facility
Features Provided:
Actuator knob
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round single actuator
Terminal Type:

Tab, solder lug

NSN 5930-00-802-2898

Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.0 amperes resistive load dc at sea level
Precious Material And Location:
Contacts and rotors silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0