## NSN 5930-00-802-3601

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-802-3601

## **Thread Class:**

3a all pressure connection

## Longest Horizontal Distance Between Mounting Centers:

0.875 inches

## Longest Vertical Distance Between Mounting Centers:

1.500 inches

## Pressure Switch Type:

Gage

## **Mounting Method:**

Base and threaded hole

## Thready Qty Per Inch (tpi):

24 all threaded hole

#### **Contact Action Stimulus:**

Increase

#### **Thread Size:**

0.4375 inches single pressure connection

## **Mounting Facility Pattern:**

Four position rectangular

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

## **Terminal Type:**

Tab, solder lug

## **Contact Load Current Rating:**

2.5 amperes resistive load single voltage

## **Contact Adjustability:**

Actuation point adjustable, preset

## **Contact Adjustment Range:**

+0.00/+30.00 actuation point pounds per square inch

## **Contact Adjustment Type:**

External actuation point screw

## Contact Voltage Rating In Volts:

250.0 dc at sea level single voltage

## Pressure Connector Type:

Plain, threaded external all connections

## **Thread Series Designator:**

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

# NSN 5930-00-802-3601

Pressure Switch - Page 2 of 2

**Fiig:** A048b0

