

View Online at <https://aerobasegroup.com/nsn/5930-00-802-3732>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Waterproof

**Overall Length:**

1.375 inches

**Overall Height:**

0.622 inches

**Overall Width:**

0.622 inches

**Body Diameter:**

0.562 inches

**Body Length:**

0.969 inches

**Case Material:**

Plastic

**Actuator Diameter:**

Between 0.370 inches and 0.377 inches

**Actuator Height:**

0.250 inches

**Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 tab, solder lug

**Specification Data:**

81349-mil-s-8805/3 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0