## NSN 5930-00-802-6676

Rotary Switch - Page 1 of 1



5930-00-802-6676

View Online at https://aerobasegroup.com/nsn/s
Thread Length:
0.375 inches single mounting facility
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.875 inches single actuator
Individual Section Quantity:
2
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section rear
Throw Quantity:
5 each section rear
Mounting Method:
Threaded bushing single mounting facility
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
120.0 dc at sea level
<b>Switch Actuator Indexing Position Quantity:</b>
Switch Actuator indexing Position Quantity.
5 single actuator
5 single actuator
5 single actuator Shaft Type:
5 single actuator  Shaft Type:  Round single actuator
5 single actuator  Shaft Type:  Round single actuator  Terminal Type:
5 single actuator  Shaft Type:  Round single actuator  Terminal Type:  Tab, solder lug
5 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action:
5 single actuator  Shaft Type: Round single actuator  Terminal Type: Tab, solder lug  Contact Switching Action:  Breaks before makes each section rear
5 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Breaks before makes each section rear Switch Actuator Positioning Increment:
5 single actuator  Shaft Type: Round single actuator  Terminal Type: Tab, solder lug  Contact Switching Action: Breaks before makes each section rear  Switch Actuator Positioning Increment: 30.0 degrees single actuator
5 single actuator  Shaft Type: Round single actuator  Terminal Type: Tab, solder lug  Contact Switching Action: Breaks before makes each section rear  Switch Actuator Positioning Increment: 30.0 degrees single actuator  Contact Load Current Rating:
5 single actuator  Shaft Type: Round single actuator  Terminal Type: Tab, solder lug  Contact Switching Action: Breaks before makes each section rear  Switch Actuator Positioning Increment: 30.0 degrees single actuator  Contact Load Current Rating: 1.0 amperes resistive load dc at sea level
5 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Breaks before makes each section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load dc at sea level Thread Series Designator:
5 single actuator  Shaft Type: Round single actuator  Terminal Type: Tab, solder lug  Contact Switching Action: Breaks before makes each section rear  Switch Actuator Positioning Increment: 30.0 degrees single actuator  Contact Load Current Rating: 1.0 amperes resistive load dc at sea level  Thread Series Designator: Unef single mounting facility
5 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Breaks before makes each section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load dc at sea level Thread Series Designator: Unef single mounting facility Shelf Life:
5 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Breaks before makes each section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load dc at sea level Thread Series Designator: Unef single mounting facility Shelf Life: N/a
5 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Breaks before makes each section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load dc at sea level Thread Series Designator: Unef single mounting facility Shelf Life: N/a
5 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Breaks before makes each section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load dc at sea level Thread Series Designator: Unef single mounting facility Shelf Life: N/a Unit Of Measure:

Fiig:

A052b0