NSN 5930-00-802-7700

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-802-7700

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
0.940 inches
Overall Width:
0.670 inches
Body Length:
1.940 inches
Body Width:
0.670 inches
Body Height:
0.860 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
1.250 inches
Actuator Style:
Leaf
Actuator Width:
0.190 inches
Actuator Free Position Height:
0.700 inches
Maximum Voltage Rating In Volts:
125.0 ac and 28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:

4.0 ounces

NSN 5930-00-802-7700

Sensitive Switch - Page 2 of 2



Switch Actuating Force	e:
------------------------	----

Between 10.0 ounces and 22.0 ounces

Actuator Movement:

Between 0.065 pretravel inches and 0.010 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0