NSN 5930-00-802-8373

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-802-8373

Thread Class: 2a single mounting facility **Overall Length:** 4.875 inches **Overall Height:** 4.125 inches **Overall Width:** 4.125 inches First Flat Length: 0.500 inches single actuator Flat Height: 0.312 inches single actuator **Shaft Diameter:** 0.375 inches single actuator **Shaft Length:** 1.125 inches single actuator **Unthreaded Mounting Hole Diameter:** 0.250 inches single mounting facility **Individual Section Quantity: Knob Manufacturer Code:** 63743 **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob **Contact Voltage Rating In Volts:** 500.0 ac at sea level **Mounting Facility Pattern:** Four position circular single mounting facility **Switch Actuator Indexing Position Quantity:** 2 single actuator **Terminal Type:** Clip **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Contact Load Current Rating:**

Special Features:

Rd flatted thd hole and pin type shaft

30.0 amperes resistive load ac at sea level

NSN 5930-00-802-8373

Rotary Switch - Page 2 of 2



Style	Desia	nator:

Circular wafer, bushing mount

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

c	h	_	ı£	•	ife	
	n	e	IΤ		ITE	•

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A052b0