NSN 5930-00-803-2722

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-803-2722 **Overall Length:** 1.260 inches **Overall Height:** Between 0.647 inches and 0.650 inches **Body Diameter:** 0.620 inches **Body Height:** 0.450 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches **Distance Between Mounting Facility Centers:** 0.880 inches **Tempurature Sensing Element Type:** Disc **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit **Mounting Method:** Bracket and unthreaded hole **Features Provided:** Hermetically sealed case **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 1.0 amperes resistive load single voltage and 750.0 milliamperes lamp load single voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 130.00 actuation point degrees fahrenheit and 140.00 actuation point degrees fahrenheit and 120.00 deactuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level single voltage Media For Which Designed: Gas or liquid **Style Designator:**

N/a

Disc w/flange Shelf Life:

NSN 5930-00-803-2722

Thermostatic Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0