NSN 5930-00-803-2820

Sensitive Switch - Page 1 of 2

Unef



View Online at https://aerobasegroup.com/nsn/5930-00-803-2820

view Online at https://aerobasegroup.com/nsii/5950-00-605-2620
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
2.761 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.781 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.120 inches
Housing Diameter:
1.000 inches
Housing Length:
0.980 inches
Housing Bushing Length:
0.800 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action single switch unit
Switch Release Force:
64.0 ounces
Switch Actuating Force:
Between 96.0 ounces and 192.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 3.000 amperes inductive dc
Thread Series Designator:

NSN 5930-00-803-2820

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0