## NSN 5930-00-803-6076

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-803-6076

| Overall Length:   |
|---|
| 1.375 inches  |
| Overall Height:   |
| 0.609 inches  |
| Body Diameter:  |
| 0.609 inches  |
| Body Height:  |
| 0.337 inches  |
| Distance Between Mounting Facility Centers:   |
| 1.125 inches  |
| Tempurature Sensing Element Type:   |
| Internal sensor   |
| Operating Tempurature Rating:   |
| 65.0 degrees celsius  |
| Mounting Method:  |
| Bracket   |
| Contact Action Stimulus:  |
| Increase  |
| Mounting Facility Pattern:  |
| Two position in-line  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, single throw, both positions maintained   |
| Terminal Type:  |
| Tab, solder lug   |
| Contact Load Current Rating:  |
| 8.0 amperes resistive load single voltage   |
| Contact Adjustability:  |
| Deactuation point not adjustable and actuation point not adjustable                     |
| Contact Stimulus Rating:  |
| 60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts:  |
| 125.0 ac at sea level single voltage  |
| Frequency In Hertz:   |
| 400.0 single voltage  |
| Media For Which Designed:   |
| Gas or liquid   |
| Style Designator:   |
| Disc w/flange   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

## NSN 5930-00-803-6076

Thermostatic Switch - Page 2 of 2



| Demi |  |  |  |
|------|--|--|--|
|      |  |  |  |
|      |  |  |  |

No

Fiig:

A048b0