

View Online at <https://aerobasegroup.com/nsn/5930-00-804-6725>

**Body Style:**

Hole mount

**Overall Length:**

Between 1.797 inches and 1.827 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.797 inches

**Overall Height:**

Between 2.510 inches and 2.644 inches

**Overall Width:**

2.130 inches

**Body Width:**

1.520 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

Between 1.031 inches and 1.155 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in and center position locked in

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

40.000 amperes resistive dc and 20.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0