

View Online at <https://aerobasegroup.com/nsn/5930-00-805-2285>

**Body Style:**

Hole mounted

**Overall Length:**

Between 0.766 inches and 0.796 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.245 inches and 0.255 inches

**Overall Height:**

Between 1.000 inches and 1.030 inches

**Overall Width:**

Between 0.485 inches and 0.515 inches

**Body Length:**

Between 0.766 inches and 0.796 inches

**Body Width:**

Between 0.360 inches and 0.390 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.084 inches and 0.094 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 0.636 inches and 0.646 inches

**Actuator Roller Diameter:**

Between 0.155 inches and 0.165 inches

**Actuator Adapter Style:**

Roller leaf

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

22.0 ounces

**Actuator Movement:**

Between 0.015 pretravel inches and 0.007 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 3.000 amperes motor ac

**Special Features:**

Wire leads 24 in. Lg

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0