

View Online at <https://aerobasegroup.com/nsn/5930-00-805-2285>

Body Style:

Hole mounted

Overall Length:

Between 0.766 inches and 0.796 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.245 inches and 0.255 inches

Overall Height:

Between 1.000 inches and 1.030 inches

Overall Width:

Between 0.485 inches and 0.515 inches

Body Length:

Between 0.766 inches and 0.796 inches

Body Width:

Between 0.360 inches and 0.390 inches

Unthreaded Mounting Hole Diameter:

Between 0.084 inches and 0.094 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 0.636 inches and 0.646 inches

Actuator Roller Diameter:

Between 0.155 inches and 0.165 inches

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

22.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.007 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 3.000 amperes motor ac

Special Features:

Wire leads 24 in. Lg

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0