

View Online at <https://aerobasegroup.com/nsn/5930-00-805-7461>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.370 inches and 0.380 inches

Overall Height:

0.835 inches

Overall Width:

0.266 inches

Body Width:

Between 0.251 inches and 0.281 inches

Unthreaded Mounting Hole Diameter:

Between 0.090 inches and 0.100 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.010 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0