

View Online at <https://aerobasegroup.com/nsn/5930-00-805-7461>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.370 inches and 0.380 inches

**Overall Height:**

0.835 inches

**Overall Width:**

0.266 inches

**Body Width:**

Between 0.251 inches and 0.281 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.090 inches and 0.100 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Adapter Style:**

Roller leaf

**Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

10.0 ounces

**Actuator Movement:**

Between 0.078 pretravel inches and 0.010 overtravel inches and 0.015 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0