

View Online at <https://aerobasegroup.com/nsn/5930-00-808-1732>

Thread Class:

3b single pressure connection

Overall Length:

2.938 inches

Overall Height:

3.125 inches

Overall Width:

3.625 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

120.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

180.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+3.00/+60.00 actuation point pounds per square inch and +3.00/+60.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

15.00 actuation point pounds per square inch and 13.00 deactuation point pounds per square inch and 2.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0