NSN 5930-00-808-4535

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-808-4535

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
0.812 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
0.844 inches
Actuator Style:
Leaf
Actuator Width:
0.250 inches
Actuator Free Position Height:
0.938 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
3.0 ounces
Switch Actuating Force:
10.0 ounces
Actuator Movement:
0.109 pretravel inches and 0.093 overtravel inches and 0.046 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 20.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

NSN 5930-00-808-4535

Sensitive Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A053a0