## NSN 5930-00-808-5707

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-808-5707

| Body Style:  |
|--|
| Lh access cover  |
| Hazardous Locations/environmental Protection:  |
| Dustproof and moisture proof   |
| Actuator Style:  |
| Roller plunger   |
| Actuator Free Position Height:   |
| 2.641 inches   |
| Actuator Roller Diameter:  |
| Between 0.646 inches and 0.666 inches  |
| Actuator Roller Width:   |
| Between 0.177 inches and 0.197 inches  |
| Housing Height:  |
| 2.156 inches   |
| Housing Length:  |
| 4.000 inches   |
| Housing Width:   |
| Between 1.125 inches and 1.188 inches  |
| Maximum Voltage Rating In Volts:   |
| 460.0 ac and 250.0 dc  |
| Inclosure Type:  |
| Fully enclosed   |
| Nonpile-up Contact Arrangement:  |
| 1 pole, double throw, both positions maintained single switch unit                       |
| Switch Release Force:  |
| 12.0 ounces  |
| Switch Actuating Force:  |
| 40.0 ounces  |
| Actuator Movement:   |
| Between 0.094 pretravel inches and 0.156 overtravel inches and 0.010 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:                                    |
| 250.000 milliamperes resistive dc and 20.000 amperes resistive ac                        |
| Terminal Type And Quantity:  |
| 3 screw  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <u></u>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A053a0   |