

View Online at <https://aerobasegroup.com/nsn/5930-00-808-5707>

Body Style:

Lh access cover

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.641 inches

Actuator Roller Diameter:

Between 0.646 inches and 0.666 inches

Actuator Roller Width:

Between 0.177 inches and 0.197 inches

Housing Height:

2.156 inches

Housing Length:

4.000 inches

Housing Width:

Between 1.125 inches and 1.188 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

12.0 ounces

Switch Actuating Force:

40.0 ounces

Actuator Movement:

Between 0.094 pretravel inches and 0.156 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0