## NSN 5930-00-808-5707

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-808-5707

Body Style:
Lh access cover
Hazardous Locations/environmental Protection:
Dustproof and moisture proof
Actuator Style:
Roller plunger
Actuator Free Position Height:
2.641 inches
Actuator Roller Diameter:
Between 0.646 inches and 0.666 inches
Actuator Roller Width:
Between 0.177 inches and 0.197 inches
Housing Height:
2.156 inches
Housing Length:
4.000 inches
Housing Width:
Between 1.125 inches and 1.188 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
12.0 ounces
Switch Actuating Force:
40.0 ounces
Actuator Movement:
Between 0.094 pretravel inches and 0.156 overtravel inches and 0.010 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 20.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
<u></u>
Demilitarization:
No
Fiig:
A053a0