

View Online at <https://aerobasegroup.com/nsn/5930-00-808-5707>

**Body Style:**

Lh access cover

**Hazardous Locations/environmental Protection:**

Dustproof and moisture proof

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

2.641 inches

**Actuator Roller Diameter:**

Between 0.646 inches and 0.666 inches

**Actuator Roller Width:**

Between 0.177 inches and 0.197 inches

**Housing Height:**

2.156 inches

**Housing Length:**

4.000 inches

**Housing Width:**

Between 1.125 inches and 1.188 inches

**Maximum Voltage Rating In Volts:**

460.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

12.0 ounces

**Switch Actuating Force:**

40.0 ounces

**Actuator Movement:**

Between 0.094 pretravel inches and 0.156 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0