

View Online at <https://aerobasegroup.com/nsn/5930-00-808-7141>

Thread Class:

2b

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.380 inches

Body Width:

0.840 inches

Body Height:

1.090 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.810 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.806 inches

Actuator Roller Diameter:

0.190 inches

Actuator Roller Width:

0.190 inches

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

End Application:

Radar, fcs, an/spg-55

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

20.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

30.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.038 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0