NSN 5930-00-809-0456

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-809-0456

Body Style:

Bushing/hole mounted

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

2.891 inches

Overall Width:

0.491 inches

Bushing Length:

0.500 inches

Body Length:

1.250 inches

Body Width:

0.491 inches

Body Height:

1.672 inches

1.072 menes

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.484 inches

Actuator Height:

0.719 inches

Actuator Free Position Height:

1.219 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

6.0 ounces

NSN 5930-00-809-0456

Sensitive Switch - Page 2 of 2



Switch Actuating Force:

40.0 ounces

Actuator Movement:

Between 0.094 pretravel inches and 0.125 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0