

View Online at <https://aerobasegroup.com/nsn/5930-00-809-2426>

**Thread Class:**

2b

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

2.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.812 inches

**Overall Width:**

1.688 inches

**Body Length:**

2.125 inches

**Body Width:**

1.688 inches

**Body Height:**

1.625 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

24.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

30.000 amperes resistive dc and 18.000 amperes inductive dc and 7.000 amperes lamp dc

**Special Features:**

Wire leads 6.000 in. Lg

**Test Data Document:**

81349-mil-s-13735 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 wire lead

**Specification Or Standard:**

4 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0