

View Online at <https://aerobasegroup.com/nsn/5930-00-809-2426>

Thread Class:

2b

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

2.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.812 inches

Overall Width:

1.688 inches

Body Length:

2.125 inches

Body Width:

1.688 inches

Body Height:

1.625 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

24.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

30.000 amperes resistive dc and 18.000 amperes inductive dc and 7.000 amperes lamp dc

Special Features:

Wire leads 6.000 in. Lg

Test Data Document:

81349-mil-s-13735 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 wire lead

Specification Or Standard:

4 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0