

View Online at <https://aerobasegroup.com/nsn/5930-00-809-2507>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.689 inches

Overall Height:

1.500 inches

Overall Width:

1.500 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.596 inches

Actuator Free Position Height:

2.239 inches

Housing Diameter:

1.500 inches

Housing Length:

1.450 inches

Housing Bushing Length:

1.640 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.500 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc and 6.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0