

View Online at <https://aerobasegroup.com/nsn/5930-00-809-2507>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

3.689 inches

**Overall Height:**

1.500 inches

**Overall Width:**

1.500 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.596 inches

**Actuator Free Position Height:**

2.239 inches

**Housing Diameter:**

1.500 inches

**Housing Length:**

1.450 inches

**Housing Bushing Length:**

1.640 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.500 overtravel inches and 0.035 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 6.000 amperes inductive dc and 6.000 amperes motor dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0