## NSN 5930-00-809-8803

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-809-8803

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.237 inches
Overall Width:
1.062 inches
Shaft Diameter:
0.124 inches single actuator
Shaft Length:
0.500 inches single actuator
Individual Section Quantity:
3
Operating Tempurature Range:
-65.0/+250.0 degrees fahrenheit
Switch Contact Basic Design:
Pile-up
Mounting Method:
Printed circuit single mounting facility
Features Provided:
Cam actuated
Pile-up Contact Form Arrangement:
1c single switch each section in-line
Contact Voltage Rating In Volts:
30.0 dc at sea level
Shaft Flat/slot Angular Location:
90.0 degrees from contact position 1 single actuator
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round, slotted single actuator
Terminal Type:
Turret
Contact Switching Action:
Makes before breaks each section in-line
Switch Actuator Positioning Increment:
48.0 degrees single actuator
Contact Load Current Rating:
5.0 amperes resistive load lowest ac voltage rating at sea level and 5.0 amperes inductive load lowest ac voltage rating at sea level
Style Designator:
In-line, cam actuated
Shelf Life:
N/a

## **NSN 5930-00-809-8803**Rotary Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A052b0