NSN 5930-00-810-9213

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-810-9213
Body Style:
Hole mounted
Overall Length:
0.876 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.390 inches
Overall Height:
0.739 inches
Overall Width:
0.346 inches
Body Length:
0.876 inches
Body Width:
0.346 inches
Body Height:
0.600 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.078 inches
Actuator Heights

Actuator Height:

0.139 inches

Actuator Free Position Height:

0.425 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 5.0 ounces and 17.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

NSN 5930-00-810-9213

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0