# NSN 5930-00-810-9213

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-810-9213

# Body Style:

Hole mounted

### **Overall Length:**

0.876 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

0.390 inches

#### **Overall Height:**

0.739 inches

#### **Overall Width:**

0.346 inches

#### **Body Length:**

0.876 inches

### Body Width:

0.346 inches

#### Body Height:

0.600 inches

## Case Material:

Plastic

## **Unthreaded Mounting Hole Diameter:**

0.088 inches

## Actuator Style:

Round

#### **Actuator Diameter:**

0.078 inches

## Actuator Height:

0.139 inches

## **Actuator Free Position Height:**

0.425 inches

## Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

## Switch Release Force:

4.0 ounces

# Switch Actuating Force:

Between 5.0 ounces and 17.0 ounces

#### **Actuator Movement:**

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

# NSN 5930-00-810-9213

Sensitive Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

# Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A053a0