

View Online at <https://aerobasegroup.com/nsn/5930-00-810-9311>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof and humidity resistant and shock proof

Bushing Length:

0.717 inches

Body Length:

1.016 inches

Body Width:

Between 0.484 inches and 0.516 inches

Body Height:

Between 0.703 inches and 0.735 inches

Case Material:

Plastic

Actuator Length:

Between 0.828 inches and 0.860 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.422 inches and 0.454 inches

Actuator Width:

Between 0.234 inches and 0.266 inches

Actuator Color:

Black all actuators

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0