NSN 5930-00-811-7110

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-811-7110

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Actuator Length:

3.500 inches

Actuator Style:

Roller arm

Actuator Height:

1.000 inches

Actuator Roller Diameter:

1.500 inches

Actuator Roller Width:

0.312 inches

Housing Height:

3.062 inches

Housing Length:

6.125 inches

Housing Width:

3.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

5.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.375 inches

Maximum Voltage Rating In Volts:

440.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 1.500 amperes resistive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5930-00-811-7110 Sensitive Switch - Page 2 of 2

Fiig: A053a0

