NSN 5930-00-811-7110

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-811-7110

Body Style:
Hole mounted

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Actuator Length:
3.500 inches
Actuator Style:
Roller arm
Actuator Height:
1.000 inches
Actuator Roller Diameter:
1.500 inches
Actuator Roller Width:
0.312 inches
Housing Height:
3.062 inches
Housing Length:
6.125 inches
Housing Width:
3.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
5.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.375 inches
Maximum Voltage Rating In Volts:
440.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Mounting Method: Unthreaded hole
-
Unthreaded hole
Unthreaded hole Nonpile-up Contact Arrangement:
Unthreaded hole Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, one position momentary single switch unit
Unthreaded hole Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage:
Unthreaded hole Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes resistive dc and 1.500 amperes resistive ac
Unthreaded hole Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes resistive dc and 1.500 amperes resistive ac Terminal Type And Quantity:
Unthreaded hole Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes resistive dc and 1.500 amperes resistive ac Terminal Type And Quantity: 4 screw
Unthreaded hole Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 0.500 amperes resistive dc and 1.500 amperes resistive ac Terminal Type And Quantity: 4 screw Shelf Life:

No

Demilitarization:

NSN 5930-00-811-7110 Sensitive Switch - Page 2 of 2



Fiig:

A053a0