

View Online at <https://aerobasegroup.com/nsn/5930-00-811-8389>

Thread Class:

2b 2nd mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

7.697 inches

Overall Height:

3.750 inches

Overall Width:

3.375 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Unthreaded Mounting Hole Diameter:

0.213 inches 1st mounting facility

Individual Section Quantity:

15

Longest Horizontal Distance Between Mounting Centers:

3.219 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

3.219 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

1 each section rear

Mounting Method:

Bracket 2nd mounting facility and threaded hole 2nd mounting facility

Features Provided:

Actuator knob

Thread Size:

0.250 inches 2nd mounting facility

Contact Voltage Rating In Volts:

450.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

1 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0